

Eopllly Blessed by the sunshine



Solar module EPTECH—156M series

Eptech 156M series solar modules are made of 72 pcs 156 mmx156 mm crystalline solar cells in series with high efficiency, high transmission rate and low iron tempered glass, anti-aging EVA and high flame resistant back sheet, and anodized aluminum alloy. The modules have advantages of high efficiency, long service life, easy to install as well as high wind and hail impact resistance.

Features and benefits

High efficiency
 Outstanding low-light performance
 Applicable for grid connected and 24V stand-alone systems
 Power warranties: 25years (80%), 10years (90%)
 10 years product guarantee
 Power tolerance +/- 3%
 Modules are protected against environmental stress by firm attachment of the module frame and glass



Solar Module

265W

EPTECH 156M

Electrical Specifications


Type / Model			
open circuit voltage (voc)	43.992	short-circuit current temperature coefficient	0.036%K
optimum operating voltage (vmp)	35.208	open-circuit current temperature coefficient	-0.346%K
short-circuit current (Isc)	8.21	peak power temperature coefficient	-0.47%K
optimum operating current (Imp)	7.52	total number of cells	72
maximum power at STC (Pmax)	265w	module total dimension L x W x T (mm)	1953 x 997 x 50
operating temperature	-40°C to 85°C	module efficiency	13.6%
Maximum system voltage	1000VDC	cell efficiency	15.2%

The electrical specifications are typical average value from historical production data.

The electrical data relates to standard test conditions [STC]: 1,000W/m²; AM 1.5; 25°C

EPTECH 156M Series

ALL DIMENSIONS IN mm



Specifications

Cell	Monocrystalline silicon solar cell 156mm x 156mm
Number of cells	72(6 x 12)
Size	1953x99x 50
Weight	26kg

Eoply New Energy Technology Co.,Ltd

Headquarter

188 West Huanghai Rd, Hai'an,
Jiangsu Province, China, 226602

Tel: +86 (513) 8878 2359

Fax: +86 (513) 8878 2383

Shanghai Business Center

Room 502 No.2 East Jinling Rd.

Guang Ming Building Shanghai 200002

Tel: +86 (21) 6323 8198

Fax: +86 (21) 6323 3323

Eoply Europe (Frankfurt Germany)

Tel: +49 (721) 830 9330

Fax: +49 (721) 830 9349

Eoply Korea

#766-1(3F) Hwanggeum-Dong,

Suseong-Gu, Daegu, Korea

Tel: +82(053) 7640 600

Fax: +82(053) 7637 706